



# LED Mini-Light Strings

All-weather, commercial-grade

Physical	
LED Quantity	1
Colors	pure white, cool white, warm white, sun warm white, red, green, blue, yellow, orange, purple, teal, pink, multi-color, custom
Housing	polycarbonate
Bulb Type	5mm wide angle, M5, T5, G12, C6 (Large lens: C9, C7, G40, G30, G20)
Lens	clear, frosted, faceted
Wire Color	black, green, white, clear
Bulb Pitch	4-, 6-, 12-inch
Bulb Count	25, 35, 50, 70, 100
Control	
Dimmable	yes
Individually Addressable	no
Shimmer or Twinkle	optional
Electrical & Safety	
Input Voltage	120 VAC
Power	0.1 Watts per pixel
Wire	22 AWG, 2C, UV protected
Wire Insulation	94-VO / PS
Connector Type	IP 65 co-axial or Edison
Certifications	(c)UL listed power supply, CE
Weatherproof Rating	IP 65
Burning Hours	approx. 40,000
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ  
Mechanicsburg, PA  
(717) 763-1055

Minleon West  
Las Vegas, NV  
(747) 221-6888

[www.minleonusa.com](http://www.minleonusa.com)



Specifications as of January 2019 and are subject to change.