



# RGB+Line Light Bar - Frosted/Wide RGB+Bar-FW

**Length:** 1-meter

**Ends:** thru-connect, terminated

**Style:** frosted

**Wire Color:** black, white, green

Output	
LED Type	SMD 5050
LED Channels	R-G-B
LED Count	48 / meter
LED/Chip	6 / 1
Chip/Meter	8
Greyscale	16-bit, 65,536 dimming levels*
Viewing Angle	180-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Bars before power injection	18
Max Distance before power injection	~60-feet / 18-meters
Electrical & Safety	
Input Voltage	24 VDC
Current	0.2 Amps / meter
Power	4.8 Watts / meter
Wire	18 AWG, 3C, UV protected
Inline power injection	via Minleon Power T's & 3A or 4A / 24V
Physical	
Size	33mm wide / 55mm depth
Pitch	0.82-inch
Housing	polycarbonate
Connector Type	LLT twist-lock
Lead/End Wire length	6" (standard)
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ  
Mechanicsburg, PA  
(717) 763-1055

[www.minleonusa.com](http://www.minleonusa.com)



\* 8-bit via DDP.

Specifications as of May 2021 and are subject to change.